

Nextthink V6.7

Product Overview

Generated: 10/14/2019 10:11 am

Table of Contents

Nextthink End-User IT Analytics.....	1
Software components.....	1
Collector.....	3
Mobile Bridge.....	6
Finder.....	6
Engine.....	7
Portal.....	7
Nextthink Library.....	7
What's new in V6.7.....	9
New features.....	9
Data-model changes.....	11
What's new in V6.6.....	13
New features.....	13
Data-model changes.....	17
Deprecated features.....	19
What's new in V6.5.....	21
New features.....	21
New HW requirements.....	24
Data-model changes.....	25
What's new in V6.4.....	29
New features.....	29
Data-model changes.....	30
What's new in V6.3.....	33
New features.....	33
Data-model changes.....	35
What's new in V6.2.....	40
New features.....	40
Data-model changes.....	43
What's new in V6.1.....	48
New features.....	48
Data-model changes.....	49

Table of Contents

What's new in V6.0.....	50
New features.....	50
New system requirements.....	51
Data-model and API changes.....	52
Deprecated features.....	52

Nextthink End-User IT Analytics


Software components

Nextthink is the innovator of End-user IT Analytics for security, ITSM and workplace transformation. Nextthink maps all the IT services, how they are being consumed, and how the IT infrastructure is operating, from the only perspective that matters most, the end-users (workers). Nextthink provides essential visibility and insight into IT operations and security for IT Governance.

Nextthink Architecture

The architecture of Nextthink has been designed to simplify operations, ensure scaling and allow a rapid deployment. The system is composed of six main software components:

- The Collector captures information from all end-user desktops and laptops.
- The Mobile Bridge captures mobile device information from Microsoft Exchange.
- The Engine aggregates Collector and Mobile Bridge information and provides real-time IT analytics.
- The Finder is the rich client application for searching and analyzing data on Engines.
- The Portal aggregates Engine information and provides dashboarding, reporting and long-term trending analytics.
- The Library is a cloud knowledge database.




Modular product structure

Nextthink offers a modular product structure that can grow with your needs. The Nextthink Platform is licensed with respect to the number of monitored physical or virtual devices and, optionally, server users. On top of the Platform, the following modules can be purchased:

- **End-user feedback** gives you the means to know the opinion of the end-users with respect to their IT environment.
- **Security** provides security related features including binary threat level and category, web threat level, category and hosting country.
- **Web & Cloud** grants access to analytics related to intranet and extranet HTTP and HTTPs web requests.
- **VDI Transformation** includes the analytics and Portal dashboards to ensure a successful VDI transformation project (coming soon for V6).
- **Integration toolkit** enables the product API and access to continuously improved integration samples, reports, etc.

Nextthink Platform as well as the modules grant access to investigations, widgets, dashboards, categories, etc. directly from the Nextthink Library, our cloud repository of content.




Collector

Introduction

The Collector is a light-weight agent based on patented technology. It captures and reports network connections, program executions, web requests, and many other activities and properties from the devices of the end-users on which it runs. It is implemented as a kernel driver and an accompanying service, offering remote and automated silent installations and negligible impact on the performance of local desktops, while minimizing network traffic.

CPU usage	Memory usage	Network traffic
<ul style="list-style-type: none"> • Less than 0.015% (in average) 	<ul style="list-style-type: none"> • Kernel: Around 500 KB • User: Around 20 MB 	<ul style="list-style-type: none"> • UDP: 0.1 - 0.3 Kbps (in average) • TCP: Depending on <ul style="list-style-type: none"> ◆ Campaigns ◆ Updates

The following figure depicts the functioning of the Collector as part of the whole Nextthink solution.



Collector components

The capability of the Collector for gathering user activity data is shared by the kernel driver and the helper service (or daemon) components. By running close to the operating system, the kernel driver detects some kinds of user activities that are only visible at this level.

Because of its additional features, the Windows version of the Collector includes more components than its Mac OS counterpart. Click to see the detailed list of components of the Collector.

Features

Multi-Platform

The Collector is available for both Windows and Mac OS operating systems. Originally developed for Windows, the Mac OS version of the Collector has some limitations with respect to its Windows counterpart. Besides Windows specific data, information on web requests and printing is not yet available in the Mac OS version of the Collector. Likewise, the automatic update of the Collector is only available in the Windows platform for the moment.

CrashGuard

Since the Windows Collector driver is a kernel-mode component, any error in its internals or its interaction with a misbehaving third-party driver can lead to system instabilities. Even with Nextthink putting as much attention as possible towards delivering bug-free software, the principle of precaution holds. The

Crash Guard feature detects every system crash and it disables the Collector driver itself if the system crashes more than three times in a row after installation.

Applies to platforms: #

Kernel traffic interception

Some applications may send and receive data to and from the network using kernel-mode components, actually hiding their network traffic from user-space monitoring applications. Being a kernel driver itself, the Windows Collector is nevertheless able to detect and report such traffic.

Applies to platforms: #

Paths aliasing

The Collector identifies commonly used paths (e.g. C:\WINDOWS\, C:\Program Files\) and other special mount locations (removable mount points, network drives) with paths aliases. For example, if the DVD-Rom drive is mounted under D:, the Collector reports an application **setup.exe** being launched from this media as **%RemovableDrive%\setup.exe**.

Detection of Engine

The Collector driver is able to detect when the Engine is not reachable in the local network. In this case, the Collector disables itself for 10 minutes.

Network interfaces supervision

The Collector detects if a network interface appears on or disappears from the device where it is installed. In this case, the Collector driver resends the whole context to the Engine. The process of adapting to a different network interface may take the Collector a few minutes.

Event logging

Main events and errors are written to either the standard Windows event logs or Mac OS logs.

On-the-fly configuration

The Collector driver parameters can be changed through the Collector Control Panel extension or the Collector Configuration tool. There is no need to restart the computer for the changes to become effective.

Related tasks

- Installing the Collector on Windows
- Installing the Collector on Mac OS

Related references

- Collector configuration tool
- Components of the Collector

Mobile Bridge

The Mobile Bridge is a server software component that gathers information about the mobile devices which connect to your Microsoft Exchange mail servers through the ActiveSync protocol. The Mobile Bridge sends all the gathered data back to the Engine, where it is organized and stored along with the information sent by the Collectors.

Thanks to the Mobile Bridge, you can keep an eye on the access status and last synchronization time of all the mobile devices in your corporate network and establish links between your mobile users and desktop users. Nexthink offers you this information and much more from a single place in a uniform way, helping you keep your BYOD infrastructure under control. Query Nexthink about mobile devices and users by applying the same mechanisms that you would use for querying about desktop devices and users.

Related tasks

- Installing the Mobile Bridge

Finder

Nexthink Finder, built upon powerful visualization techniques, is the search and user interface to render visibility into your IT infrastructure. Analyze IT services and query what you need within seconds. Expand or drill-down the results in a few clicks to reveal swiftly, across the entire network, how many versions of a particular application are in use and on which workstations, the bandwidth consumed by the application, the servers and domains that the application accesses, the network response times, which users experienced issues, and much more.

Engine

Nextthink Engine is a high-performance analytics software capable of processing millions of endpoint activities in seconds. Events sent in real time by Collectors populate the Engine with activity data, furnishing a rich repository of historical and live IT infrastructure usage data from the end-user perspective. Engine leverages an in-memory database for rapid queries (via the Nextthink Finder) and flexible reporting (via the Nextthink Portal).

Related tasks

- Installing the Appliance

Portal

Nextthink Portal is the reporting tool, collaboration platform and centralized management platform of the Nextthink End-User IT analytics platform. A comprehensive set of dashboards are delivered out-of-the-box but it is possible in a matter of minutes to construct custom dashboards, valuable for anyone in the organization. Personalized metrics are simple to define as drag-and-drop widgets and can be quickly published and shared. Nextthink Portal front-end is a web application running inside a browser.

Related tasks

- Installing the Appliance

Nextthink Library

The Nextthink Library is an online knowledge database that gives you access to theme-based files, a large set of ready-to-use predefined investigations, templates, dashboards and application information accessible directly from the Finder and the Portal.

A separate component of the Nextthink Library is the Application Library. The Application Library helps you identify potential threats by submitting the digital footprint of any application found on a desktop or visited web domain to its reference databases. Thanks to the full integration between the Application Library and the Engine, your infrastructure information is always fully up-to-date, without the need for any manual interaction.

Related references

- [Nextthink Library](#)
- [Nextthink Application Library](#)


What's new in V6.7

New features

End-User Feedback Module

The Nextthink End-User Feedback Module introduces a new way for IT to interact with the end-user, understand their needs and provide services that better align to business needs. By using this module, IT departments will be better able to:

- Discover user satisfaction levels with IT and the needs of end-users
- Understand how to improve the business productivity of end-users
- Quantify the true business impact of problems
- Get feedback during project, changes and transformation projects




Subjective end-user data can be analyzed together with the hundreds of metrics currently reported by Nextthink Collector to obtain true end-to-end visibility on both endpoint and infrastructure performance as well as end-user perception and satisfaction. This unique combination is key not only to understand what is happening but also to extract concrete action items to resolve problems and improve IT satisfaction.

If you are interested in learning more about the End-User Feedback Module and Nextthink's End-User Experience Improvement Solution please contact your Nextthink partner or account manager.

Find out more

Scores

Nextthink provides hundreds of metrics that can be used to measure endpoint and infrastructure performance at a technical level, but how can this information be used to understand the big picture and define KPIs that can be tracked over time? This is where the concept of score comes in. A score is a higher level indicator obtained by weighing several technical factors together.



With Nextthink you can build scores on endpoint performance, infrastructure health, service quality, and many more. Moreover, all scores can be customized to meet your needs. Scores are computed for individual devices or users and are aggregated across the whole environment to provide an understanding of the overall context. They can be broken down by region and analyzed as they evolve during time. To obtain more information about scores and customizing them for your environment, please contact your Nextthink Customer Success Services representative.


Other changes

Advanced tooltip

Our new Portal tooltip allows you to obtain more details about the indicators shown in your dashboards. The tooltip has been standardized for KPI, table and bar chart widgets. It shows the following data:

- Precise representation of the value, for instance, 1149 devices instead of 1.15k
- Details for ratios, for instance, to understand that 4.3% means 4 devices out of 93

- Variation with respect to the previous value
- Threshold, if one has been defined in the corresponding metric
- When applicable, links to access Finder and details



Find out more

More on bar charts

The bar charts introduced in the previous versions have been enhanced with support for quantity metrics, thresholds and fixed scale.

Find out more

Restrictions on default encryption protocols for Engine

We have introduced some restrictions to prevent the establishment of connections using obsolete encryption protocols to/from Engine. Starting with V6.7 by default Nextthink Engine will only support TLS1.1 or later. In most environments this should not have an impact, however we encourage you to validate that all external integrations - including LDAP - are still working correctly after upgrade.

Counting all users and devices - confirmed

Thanks to the very positive feedback, the new feature introduced as beta in the V6.6 Portal, allowing a count of all users and devices has been confirmed. It is now officially part of the product.

Data-model changes

Deprecated fields

In V6.7 there are two deprecated fields:


- Windows 7 (32-bit) compatibility
- Windows 7 (64-bit) compatibility

What's new in V6.6

New features

Bar charts

Comparing data is made trivial with the new bar chart! A bar chart can be processed pre-attentively; in other words it allows you to compare values subconsciously, without having to dwell on it. Hence, prefer bar charts to compare values and reveal the "shape" of your data, but stick to tables for looking up a specific value.



Find out more

Counting all users and devices (beta)


Nextthink Portal has been enhanced with a new way of computing metrics related to inventory use cases. Until now all values shown in Portal were computed by considering *active* objects. For instance a metric counting *Windows 10 devices* returns the number of devices running Windows 10 that were turned on during the period of time specified by the user (for instance a specific day). When it comes to inventory use cases however it might be more interesting to count all *known* devices with Windows 10 installed regardless of the fact that they were turned on or not. With V6.6 it is now possible to define such metrics for both users and devices.

This feature is available for all V6.6 installations, however we have decided to consider it in *beta* state while we evaluate users' response. We would love to hear your opinion at beta@nextthink.com!

Find out more

Finder display field selector

Finder just became more user friendly! When running investigations you need to pick out which fields to display among the hundreds that Nexthink provides. We have introduced a brand new selector that makes it possible to quickly search fields instead of manually navigating a complex menu. Moreover all fields are now better organized thanks to an improved categorization.



Find out more

New delivery model


Want to always have the latest features but find it difficult to keep up with the updates? We have drastically improved our delivery model and hope you find it easy to stay on the cutting edge.

Appliance update and federation

By default the product will remain automatically up-to-date, providing you with all the new features, benefits and security patches introduced in new releases. Moreover, advanced configuration settings allow you to define an update policy that matches internal requirements.

On top of the update policy, other configuration settings can now be automatically replicated across different appliances thus simplifying the


management of the Nexthink platform. The Nexthink Console has been completely reorganized to make the administration job even easier.



Find out more

Finder installer and auto-update

Introduced in beta in V6.5, the new Finder has now been confirmed. Installing the Finder has never been so easy thanks to our new install & update mechanism. Nexthink users with Finder access just need to sign in to the Portal and select **Install Nexthink Finder** after clicking on their username.



1 Sign in to Nexthink Portal

2 Install Nexthink Finder from the menu

After that, it is just a question of launching the downloaded installer. This will start the Finder with pre-configured settings to connect to your Portal. From this point on, the Finder will update itself, seamlessly even if newer versions of the Portal and the Engine are installed.

Find out more about installing the Finder and updating the Finder.

Install and forget Collector (preview)

After the first installation, you will never have to think about Nextthink Collectors again. Starting from V6.6, Collectors are in fact able to update themselves by retrieving the latest version from their Engine. As for the Appliances, extensive configuration options allow you to apply the update policy that will best suit your company.

Find out more

New hardware requirements

The hardware requirements for the Nextthink Engine have been increased to accommodate the new delivery model. All V6.6 (and later) installations must now conform to the specification described in the hardware requirements page.

Other changes

NXQL limits

The 7-day limit imposed for certain NXQL queries has now been lifted. Developers however should pay attention to potential performance impact of running a large number of highly complex queries.

Finder and Windows Vista

Windows Vista is no longer supported to run Nextthink Finder V6.6. As Vista is no longer actively supported by Microsoft and its usage share is extremely low, we hope this should not be an issue to our users. In case you are still using this platform, we encourage you to move to a newer operating system to continue receiving the latest Nextthink versions and features.

Find out more

SHA-1

SHA-1 is now available on top of MD5 for binaries. This new field does not require a Collector update.

Data-model changes

SHA-1

SHA-1 is now available on top of MD5 for binaries. This new field does not require a Collector update.

Field	Group	Type	#	🍏	📱
SHA-1 hash	Properties	Field	#	🍏	📱
Indicates the SHA-1 hash of the binary.					










New and deprecated Collector Update fields

Starting from V6.6, the Collector is now capable of updating itself by retrieving the latest version from the Engine. With this enhancement the Nexthink Updater is now redundant, and it has therefore been deprecated. As a result, there are some new fields relating to the Collector's ability to update itself, and some deprecated fields that related to the Updater.

New Collector update fields

The following fields have been added to support the Collector's ability to update itself:

Field	Group	Type	#	🍏	📱
Target version	Nextthink Collector	Field	#	🍏	📱
Indicates the Collector package version that is targeted.					
Collector update group	Nextthink Collector	Field	#	🍏	📱
Indicates the update group of Nextthink Collector:					
<ul style="list-style-type: none"> • manual: the Collector is manually updated • pilot: the Collector is updated as part of the pilot group • main: the Collector is updated as part of the main group. 					

Collector status	Nexthink Collector Field   
	<p>Indicates the status of the Nexthink Collector package installed on the device:</p> <ul style="list-style-type: none"> • unmanaged: the Collector is not automatically updated • up-to-date: the Collector is up-to-date • outdated: a newer Collector version is available.
Last update	Nexthink Collector Field   
	<p>Indicates the last Collector update time.</p>
Last update status	Nexthink Collector Field   
	<p>Indicates the status of the last Collector update:</p> <ul style="list-style-type: none"> • '-': the Collector was never updated • successful installation: the last Collector installation was successful • package download error: the Collector was not able to download the Collector package from Nexthink Appliance • package digital signature error: the Collector was not able to check the Collector package digital signature • device reboot required: the device needs to be rebooted to complete the Collector installation • package error: the Collector package

	<p>installation has failed</p> <ul style="list-style-type: none"> • internal error: the Collector package installation has failed for an unexpected reason.
--	--

Deprecated Updater fields

The following fields relating to the Updater have been deprecated:

- Updater version
- Collector update status
- Last Updater request
- Updater error
- Collector installation log

You can still enable these fields to check the update status of your old Collectors.

Related tasks

- Viewing Collector deprecated fields

Deprecated features

Applies to platforms: #

Updater

The existing Nexthink Updater is not able to upgrade Collectors to V6.6.

Since V6.6, Collectors have the intrinsic ability to update themselves. The Nexthink Updater has therefore been deprecated. Customers relying on the Updater to maintain their Collectors up-to-date are required to either:

- Use the executables generated by the Nexthink Collector Installer to deploy the Collector. These executables automatically remove the deprecated Updater when installing the new Collector.
- Remove the Updater from any device before deploying the Collector on it by means of the MSI. Uninstall the Updater via the Windows **Settings** (Control Panel) or using your favorite deployment tool. The MSI fails to install the Collector on those devices where the deprecated Updater is still present.

Force Collector installation on Servers

Every generated Collector installer is now able to install the Collector on any kind of device, be it a laptop, a desktop, or a server. The MSI parameter **DRV_FORCE_SERVER**, which was required to be set to 1 for installing the Collector on servers, has been deprecated and is no longer available.

Running multiple Engines on the same Appliance

Since the Engine is a very demanding application in terms of computing power, the possibility of running more than one Engine in the same Appliance has been ruled out.

Related tasks

- Updating the Collector

Related references

- Collector MSI parameters reference table

What's new in V6.5

New features

Improved boot and logon duration metrics

We have introduced several changes to improve the accuracy and usefulness of boot and logon duration metrics: boot values are now more precise and for user logon we now distinguish between an objective measurement representing the desktop being shown and a subjective measurement representing the device being optimally ready for use. More details are available in the Data-model changes page.

More granularity for visualizing CPU activity

In V6.4 we introduced a new device warning event called **High overall CPU usage** to better represent situations of high CPU consumption. This event is triggered when 70% of all logical processors are used, or in other words, when at least 70% of the total CPU capacity of the device is consumed.

In V6.5 we have modified the user and device views to include this event.

In **blue**: Specific applications are impacted

Tuesday, 28. June 2016
11:40 - 45

High application CPU usage

- motty.exe (MobaXterm terminal): 93% for 4min 59s out of 800% for this device.

[Know more...](#)

Warnings
High CPU usage 2h 7min 7s

In **yellow**: the whole device is impacted

Monday, 27. June 2016
16:02:02 - 16:08:32

High device CPU usage

70% of the total CPU capacity was used for 30s.

High application CPU usage

- searchindexer.exe (Windows Search): 122% for 2min 30s
- boxesync.exe (Box Sync): 59% for 30s
- searchprotocolhost.exe (Windows Search): 52% for 30s out of 800% for this device.

[Know more...](#)

In the case of long lasting *blue* warnings: specific applications are consuming a large amount of CPU, but the overall device experience is not compromised. It can be interesting to investigate these situations because the high CPU usage might be abnormal and indicate an issue with specific applications. Moreover, battery life of laptops may be drastically compromised by applications that consume an elevated amount of CPU for long periods of time.

In the case of long lasting *yellow* warnings: the user experience is likely to be impacted and further analysis is recommended to identify and resolve the problem.

In both cases, the tooltips might offer additional insights into the applications causing the issues.

Find out more

Other changes

Metrics access rights

A new configuration setting allows you to more precisely control which Portal metrics users are allowed to access.

The screenshot shows a dialog box titled "Edit profile (step 1)". It contains a text input field for "Profile name" with the value "Lausanne user". Below this is the "Account type" section with radio buttons for "User", "Administrator", and "Central administrator". The "User" option is selected, and a checked checkbox "Allow creation of personal dashboards" is visible. A new section, "Available metrics", is highlighted with a red box and labeled "New area". It contains two radio button options: "All metrics" (selected) and "Only metrics in roles". At the bottom of the dialog are "Cancel" and "Next" buttons.

Migration considerations: the system will automatically choose a value to ensure that no user is given access to metrics that he could not access before the upgrade.

Find out more

New hardware requirements

The hardware requirements for the Nexthink Engine have been increased to accommodate upcoming features. Beginning with V6.6 (September 2016), up to 2GB of RAM and 2 CPUs should be added depending on your configuration.

Find out more

New connectivity requirements

Beginning with this version, both the Nexthink Engine and the Portal will connect to the Nexthink Application Library (in previous versions only the Engine was connecting).


Find out more

New Engine certificate

The default Engine certificate used to establish secure connections between the Web API, Finder, and Portal has been updated. For installations using the default certificates, users who saved the certificate in Finder or in the web-browsers will now again be asked to add an exception.

New Finder install and update mechanism, in beta

Installing the Finder has never been so easy thanks to our new install & update mechanism. Nexthink users with Finder access just need to log in to the Portal and select **Install Nexthink Finder** after clicking on their username.



After that, it is just a question of launching the downloaded installer, which will then directly start the Finder and configure it to connect to the right Portal.



From this point forward, the Finder will be automatically and transparently updated, even in case of new releases of the Portal and the Engine.

Find out more about installing the Finder and updating the Finder.

New HW requirements

Overview

The hardware requirements for the Nextthink Engine have been increased to accommodate upcoming features. Beginning with **V6.6 (September 2016)**, up to 2GB of RAM and 2 CPUs should be added depending on your configuration.

If you have an existing installation, you do not have to worry, as you will be able to upgrade and run the latest version of the product without upgrading your hardware. However, you should be aware that you will not be able to turn on the new features until the new requirements are met.

It is very important that new installations observe the new requirements and that you upgrade existing installations whenever you have the opportunity.

Check the new hardware requirements for multi-appliance set-up and for single-appliance.

FAQ

What are the new requirements?

We have two sets of new requirements:

- **Minimum:** these requirements must be implemented so the product runs smoothly. If customers are not able to implement the new minimum requirements, it will not be possible for Nexthink to provide technical support.
- **Recommended:** these requirements should be implemented to increase product performance and provide an extra buffer for future enhancements.

Should I use the minimum or the recommended requirements?

Whenever possible, we suggest that you implement the higher recommended requirements.

When are the requirements changing?

The new minimum and recommended requirements will change in V6.6 (September 2016), but new and existing installations should implement the new requirements as soon as possible.

What should I use for new installations?

You should use the new minimum requirements or (better) the recommended requirements. The goal is that the installation is ready for 6.6 and later.

What will happen if I upgrade existing installation to 6.6, but I do not meet the minimum requirements?

No worries, the product will still work, but you will not be able to turn on the new features.

Why have we increased the minimum requirements?

New features will be released during the second half of 2016 and the beginning of 2017. These features will require more memory and CPU.

The requirements have not changed for many years, but the technology has evolved. It is necessary to implement the new requirements to provide a superior user experience and take advantage of the new features.

Data-model changes

Improved boot and logon duration metrics

Changes for event system boot

Boot duration accuracy has been improved by modifying the process used to define the completion of the boot process. Please note that this improvement does not require a new version of the Collector.

Field	Group	Type	⌘	🍏	📱
Duration	Properties	Field	⌘	🍏	📱
Indicates the time between the kernel start and the launch of the 'logonui.exe' process					

Find out more

Changes for user logon

To improve the accuracy of the logon duration we have introduced two changes.

A new definition for logon duration: in previous versions of the product the logon duration represented the moment in time when the CPU usage dropped below a certain threshold. Although this could be used to judge the user experience, the value was too open to interpretation and discussion. For this reason we have modified the measurement to report a more objective value: the logon duration now represents the time elapsed between entering the credentials and the desktop being shown to the user.

Extended logon duration: a subjective measurement of the logon duration is still very useful to analyze the user perception and experience. For this reason we have introduced a second measurement called **Extended logon duration**. This measurement represents the time needed for the device to become optimally usable after a logon. To obtain this value we measure CPU and disk usage.

Please note that a new version of the collector is needed for part of this feature.

Find out more

Field	Group	Type	⌘	🍏	📱
Duration	Properties	Field	⌘	🍏	📱

	Indicates the time between the user logging on and the desktop being shown.					
new Extended duration	<table border="1"> <tr> <td>Properties</td> <td>Field</td> <td>☰</td> <td>🍏</td> <td>📄</td> </tr> </table> <p>Indicates the time between the user logging on and the device being ready to use. Desktops and laptops are considered fully functional once the CPU usage drops below 15% and the disk usage drops below 80%. Servers are considered fully functional once the CPU usage of all processes belonging to the corresponding user drops below 15%.</p>	Properties	Field	☰	🍏	📄
Properties	Field	☰	🍏	📄		

Find out more

New fields and aggregates for devices

Field	Group	Type	☰	🍏	📄
Last logon duration	Startup	Field	☰	🍏	📄
	Indicates the last recorded value for the time between the user logging on and when the desktop is displayed.				
new Last extended logon duration	Startup	Field	☰	🍏	📄
	Indicates the last recorded value for the time between the user logging on and the device is ready.				
Logon duration baseline	Startup	Field	☰	🍏	📄
	Indicates the logon duration averaged over the last logons. In the calculation, recent logons weigh more than older logons (exponentially weighted moving average).				
new Extended logon duration baseline	Startup	Field	☰	🍏	📄
	Indicates the extended logon duration averaged over the last logons. In the calculation, recent logons weigh more than older logons (exponentially weighted				

	moving average).				
Average logon duration	Startup	Aggregate	■	🔊	📄
	Indicates the average logon duration.				
new Average extended logon duration	Startup	Aggregate	■	🔊	📄
	Indicates the average extended logon duration.				

Migration considerations

After migrating to the new version, the following changes can be expected due to the new definition and calculation of boot and logon duration:

- Average boot duration values are expected to grow
- Average logon duration values are expected to drop significantly since desktops are always shown before the CPU drops

Customers wishing to continue to measure logons based on a subjective value (representing the device being ready) instead of an objective value (representing the desktop being shown) must modify metrics and investigations to use **Extended logon duration** instead of **Logon duration**.

What's new in V6.4

New features

Investigate in Finder

A lot of the power and ease of use of Nextthink relies on the fact that Finder users can always *drill-down* to find out more information about a specific topic. Drill-downs in fact allow us to understand who is impacted by an issue, discover the dependencies between CIs and observe the exact events that lead to a specific situation.



It's only logical to extend such functionality to the Portal as well. From now on you will be able to click on any value shown in Portal to **Investigate in Finder**. This feature is so seamlessly integrated that in a matter of hours you will ask yourself *How could I work without this before?*

Find out more

More scalability and speed for Engine

Scalability and speed are crucial topics for us and breaking existing limits has become one of our preferred obsessions. We are excited to announce that V6.4 Engines will support double the number of concurrent Finder users compared to V6.3, and we will do so with the same hardware! Moreover we have drastically improved the scalability of the product; if you want more speed you just need to add 1 CPU core for each 5 Finder users.

But this was not enough... scaling more is great but we also wanted to give you more speed. So, once again, without having to change any of your hardware, you will discover that V6.4 queries take in average 30-40% less time to complete!

Find out more about the Engine hardware requirements

Other changes

Collector tag for entities

The Collector tag (a value that can be set during Collector installation and is then reported by the Collector to the Engine) can now be used in Entity rules.

Find out more about setting collector tags and using collector tags

A new option for the nxt:// protocol

A new option for the nxt:// protocols enables you to open the device/user view with a specific time frame.

Find out more

User-Device views navigation

When navigating from the user view to the device view or vice versa, the time frame is kept.

Data-model changes

Average memory usage per execution

Introduced in V6.3 and previously restricted to objects of type Executable and Binary, this aggregate has now been extended to support the following objects:

- Users
- Devices
- Applications
- Executables
- Binaries

Field	Group	Type	⌘	🍏	📱
Average memory usage per execution	Activity	Aggregate	⌘	🍏	📱
	Indicates the average memory usage of all underlying executions before aggregation. The value is the average				

	<p>memory usage of all executions (calculated with a 5-minute resolution) multiplied by their cardinalities and divided by the total cardinality.</p> <ul style="list-style-type: none"> • Example: if two tabs of the Chrome browser are opened at the same time, two distinct processes of chrome.exe are launched and they are aggregated by the Engine (i.e., event cardinality = 2). The average memory usage will be the average of the two processes before aggregation: it represents the average memory usage of a Chrome tab.
--	--

Find out more

High CPU usage changes

A new device warning event called **High overall CPU usage** has been introduced to better represent situations of high CPU consumption. This event is triggered when 70% of all logical processors are used, or in other words when at least 70% of the total CPU capacity of the device is consumed. This value is configurable.

The aggregate **High device overall CPU time ratio** represents the ratio of time where the device suffers from high overall CPU usage.

Field	Group	Type	⌘	🍏	📱
High device overall CPU time ratio	Warnings	Aggregate	⌘	🍏	📱

Indicates the ratio between the time that the device is in high overall CPU usage and its uptime.

Deprecated fields and aggregates

To simplify high CPU events following the introduction of the new **High overall CPU usage** event, the following events and aggregates have been deprecated:

- The event **High CPU usage** has been renamed to **High thread CPU usage** and has been deprecated.
- The aggregate **High CPU time** has been renamed to **High device thread CPU time ratio** and has been deprecated.







Please note that CPU warning events in the user and device views still refer to High thread CPU usage and have not yet been ported to High overall CPU usage)

Find out more

High application thread CPU time ratio

This new aggregate can be used to identify applications generating a large volume of **High thread CPU usage** events, or in other words applications with high CPU usage peaks. This aggregate is available for the following objects:

- Applications
- Executables
- Binaries

Field	Group	Type			
High application thread CPU time ratio	Warnings	Aggregate			
Indicates the ratio between the time that the underlying executions are in high thread CPU usage and their execution duration.					


Find out more

What's new in V6.3

New features

Email digests

The email digest gives you a concise update on what happened during the past week. You certainly have several areas of responsibility; for instance you may be monitoring dashboards in both "Shadow IT" and "Malware protection" modules, or many more.



The digest gives you an overall summary of the status of your modules based on what you consider your most important metrics.

Find out more

Improved features for content creators

In this release we have included two features targeted especially to Nextthink content creators.


Run metric as investigation

It is now possible to run metrics just as if they were investigations. The Finder can automatically translate any metric into an investigation and run it, letting you quickly verify the data computed by the metric. This feature is available from both the metric context menu in the accordion and the metric designer.

Export nxt:// actions

The nxt application protocol provides you with the means to launch the Finder and perform some specific actions on it by just stating a URL. Creating nxt:// links is not always trivial however. For this reason, we have now added the ability to export contextual nxt:// links directly from the **Export** menu of the following accordion objects:

- Investigations: export a link that will execute the investigation, even if you have not imported it yet. This feature is incredibly useful to quickly share investigations or embed them in an email or document.
- Services: export a link that will open the service view.
- Metrics: export a link that will open the metric designer.
- Categories: export a link that will open the category designer.



Other changes

More history, now by default in the product

With V6.3 everyone will automatically benefit from the data history optimizations we introduced in V6.1. In fact the default aggregation policy will be automatically changed to **medium**, ensuring more history and an overall faster product. If you prefer to keep things unchanged, you can go back to **low** or **very low** directly from the Web Console.


Find out more

High DPI displays now supported by Finder

High DPI displays are becoming more and more common, especially among laptops. When your display packs 5M pixels on 13 inches however, chances are that you want to increase your zoom level in Windows. Previously, the Finder had some trouble to deal with zoom levels greater than 125%. All of that has been solved now, so you can enjoy the Finder at any high resolution and zoom factors.

SSO in beta

Active Directory SSO is now available as a beta feature for the Portal. Gone are the days when you needed to type your username and password to access your favorite dashboards. With this feature enabled, and provided that you logged in to your computer as a domain user (AD account), you can access the Portal with just one single click. Did we manage to interest you? You can contact beta@nextthink.com to receive detailed instructions on how to activate this feature.



The image shows a login form for Nextthink. At the top is the 'nextthink.' logo. Below it are two input fields: 'Username' and 'Password'. Under the 'Username' field is a checkbox labeled 'Remember me' which is checked. To the right of the 'Password' field is a 'Sign in' button. Below the 'Sign in' button is a link that says 'or connect using Single Sign On'.

Data-model changes

CPU of each execution

Starting from this release, Engine will store the CPU consumed by each program execution. The corresponding data can be extracted using the two following aggregates that apply to:

- Users
- Devices
- Applications
- Executables
- Binaries

Field	Group	Type	☰	🍏	📱
Total CPU time	Activity	Aggregate	☰	🍏	📱
<p>Indicates the sum of the CPU time of all executions on each device in scope and over all logical processors.</p> <ul style="list-style-type: none"> • Example: if we consider two executions with the first one taking 50% of a logical processor during 30 minutes and the second one taking 100% of 2 logical processors during 60 minutes, the total CPU time is 135 minutes ($= 50\% * 30 \text{ min} + 2 * 100\% * 60 \text{ min}$). 					
CPU usage ratio	Activity	Aggregate	☰	🍏	📱
<p>Indicates the sum of the CPU time of all executions on each device in scope over all logical processors divided by their total duration.</p> <ul style="list-style-type: none"> • Example: if we consider two executions with the first one taking 50% of a logical processor during 30 minutes and the second one taking 100% of 2 logical processors during 60 minutes, the CPU usage ratio is 150% ($= [50\% * 30$ 					

	$\text{min} + 2 * 100\% * 60 \text{ min}] / [30 \text{ min} + 60 \text{ min}])$
--	---

Moreover this data is also available in execution events:

Field	Group	Type	⌘	🍏	📱
Total CPU time	Activity	Aggregate	⌘	🍏	📱
<p>Indicates the sum of the CPU time of all executions on each device in scope and over all logical processors.</p> <ul style="list-style-type: none"> • Example: if we consider two executions with the first one taking 50% of a logical processor during 30 minutes and the second one taking 100% of 2 logical processors during 60 minutes, the total CPU time is 135 minutes (= 50% * 30 min + 2 * 100% * 60 min). 					

Memory of each execution

Starting from this release, Engine will store the memory consumed by each program execution. The corresponding data can be extracted using the following aggregates that applies to:

- Executables
- Binaries

Field	Group	Type	⌘	🍏	📱
Average memory usage per execution	Activity	Aggregate	⌘	🍏	📱
<p>Indicates the average memory usage of all underlying executions before aggregation. The value is the average</p>					

memory usage of all executions (calculated with a 5-minute resolution) multiplied by their cardinalities and divided by the total cardinality.

- Example: if two tabs of the Chrome browser are opened at the same time, two distinct processes of chrome.exe are launched and they are aggregated by the Engine (i.e., event cardinality = 2). The average memory usage will be the average of the two processes before aggregation: it represents the average memory usage of a Chrome tab.

Moreover this data is also available in execution events:

Field	Group	Type	#	🍏	📱
Average memory usage	Properties	Field	#	🍏	📱
<p>Indicates the average memory usage of the underlying executions before aggregation with a sampling resolution of 5 minutes.</p> <ul style="list-style-type: none"> • Example: if two tabs of the Chrome browser are opened at the same time, two 					

	<p>distinct processes of chrome.exe are launched and they are aggregated by the Engine (i.e., event cardinality = 2). The average memory usage will be the average of the two processes before aggregation: it represents the average memory usage of a single Chrome tab.</p>
--	--

New field

The following field has been added:

Field	Group	Type	⌘	🍏	📱
Hard disks manufacturers	Local drives	Field	⌘	🍏	📱
	Indicates the list of hard disk manufacturers				

Changes in packages

Starting from Nextthink V6.3, those investigations retrieving packages or including a condition on packages have been simplified. The results take into account only those packages that are effectively installed, discarding uninstalled packages.

Find out more

Deprecated fields

The following fields of Binary have been deprecated in favor of the more expressive aggregates presented above:

- Average CPU usage
- Average memory usage


What's new in V6.2

New features

V6.2 comes with a wealth of new features aimed at simplifying and improving the use of the product. Moreover, we did substantial work on further optimizing Engine performance.

Dashboard description

John, the Nextthink administrator at Acme Corp. (a fictitious customer), has just finished creating a great dashboard that can be used to discover and track the usage of Shadow IT products in the organization. He wants to share this dashboard with several people in the IT team, but he's afraid that without some explanations not everyone will be able to fully understand the content and how to use it.



With V6.2 John can now write documentation directly inside of Portal and even create links to investigations in Finder. Thanks to this feature John is sure that everyone will be able to fully understand the risks posed by Shadow IT. Just like our user John, you too can now make sure everyone can fully understand the content of your dashboards.

Find out more


Microsoft DirectAccess support

DirectAccess is a technology from Microsoft that allows remote users to securely access internal network file shares, Web sites and applications without connecting to a VPN. DirectAccess works by creating a IPv6 tunnel from the remote PCs to the DirectAccess server. Starting from V6.2 all Nexthink components are able to communicate in a DirectAccess environment; moreover Collector will report network and web traffic transiting through a DirectAccess tunnel.

Find out more

Details in the past

Nexthink Portal allows you to track the evolution of your metrics for an unlimited period of time. Moreover, for metrics of type *count*, additional details about the involved objects are also available. For instance, if you click on a metric tracking the number of devices infected by malware, you will see the full list of infected machines. These details were, until today, limited to the current timeframes (yesterday, current week, current month, current quarter).



The latest version of Portal allows you to reserve additional disk space on the Portal appliance to store details for a longer period. If you want more data, you just need to add more disk space.

Find out more

Portal on your Operation Center big screens


Thanks to the real-time service overview dashboard introduced in V6.0, Portal is the ideal product to be displayed on your Ops Center big screen. To facilitate this use case, you can now configure a special account so that it's never signed out from Portal.

This gets even better when you want to display multiple dashboards in a slideshow. There are a number of free browser plugins that allow you to do just that!

Find out more

Improved Smart Search

The Finder search is getting even smarter. The system now provides suggestions based on services names and entities; for instance you can search for *users of SAP* or *devices in Dublin or Rome*.



In addition, we've added a set of new suggestions:

- New binaries/applications/executables
- Application Library fields
 - ◆ Domains classified as ? [e.g. Malicious domains]
 - ◆ Domains hosted in ? [e.g. Domains France]
 - ◆ Binaries classified in ? [e.g Binary virtualization]
- All servers
- Devices with low network availability
- Devices with high network response time
- Search user with full name (AD)

Find out more

Faster investigations

V6.2 comes with an Engine optimized for speed. Investigations will run up to 3.5 times faster thanks to increased parallelism during the computation of complex investigations and some code-level performance optimizations. You can accumulate this with the aggressive aggregation policies introduced in V6.1 for an even greater performance gain. Existing customers can contact Nextthink

Customer Success Services to discuss the best data optimization strategy for their infrastructure.

Other features

Improved access rights

We improved the way access rights are assigned. Now any *central administrator* can be given exactly the same rights as the *main central administrator*. Note that by default all *central administrators* will automatically gain the right to manage licenses. Central administrators with the *system configuration* right will automatically be able to publish Web API investigations and trigger a manual Engine AD sync. Find out more

Security improvements

When installing the product for the first time, HTTPS is the default Portal setting. Legacy HTTP access can still be activated in the Nextthink console.

nxt:// protocol

We've added two additional commands to the *nxt://* protocol which allow you to edit metrics and categories. Find out more

Default aggregation policy

The default aggregation policy has been changed to *normal*. In general this increases the available Engine history by up to 10%.

Full traffic anonymization

Whether you need this for your pre-production environment or to comply with your privacy policy, you can now chose to completely anonymize Collector traffic, even before it reaches the Engine. Find out more

Data-model changes

Nextthink V6.2 comes with 10 new aggregates to get better and faster answers out of the product.

Application stability

These two aggregates can be used to identify your least stable applications, even if they are used by just a few users. These aggregates are available for the following objects:

- Users
- Devices
- Applications
- Executables
- Binaries

Field	Group	Type	⌘	🍏	📱
Application crash ratio	Errors	Aggregate	⌘	🍏	📱
	Indicates the number of application crashes per 100 executions.				
Application not responding event ratio	Errors	Aggregate	⌘	🍏	📱
	Indicates the number of application not responding events per 100 executions.				

Incoming and outgoing network traffic per device

These two aggregates can be used to identify applications that are generating a large amount of network traffic, even if they are used by just a few users. These aggregates are available for the following objects:

- Applications
- Executables
- Binaries
- Ports
- Destinations

Field	Group	Type	⌘	🍏	📱
Incoming network traffic per device	Volume	Aggregate	⌘	🍏	📱
	Indicates the incoming network traffic divided by the number of devices.				
Outgoing network traffic per device	Volume	Aggregate	⌘	🍏	📱
	Indicates the outgoing network traffic divided by the number of				

devices.

Incoming and outgoing web traffic per device

These two aggregates can be used to identify applications that are generating a large amount of web traffic, even if they are used by just a few users. These aggregates are available for the following objects:

- Applications
- Executables
- Binaries
- Ports
- Destinations
- Domains

Field	Group	Type	⌘	🍏	📱
Incoming web traffic per device	Volume	Aggregate	⌘	🍏	📱
	Indicates the incoming web traffic divided by the number of devices.				
Outgoing web traffic per device	Volume	Aggregate	⌘	🍏	📱
	Indicates the outgoing web traffic divided by the number of devices.				

Total network and web traffic

These two aggregates can be used to compute the total web or network traffic. These aggregates are available for the following objects:

- Users
- Devices
- Applications
- Executables
- Binaries
- Ports
- Destinations
- Domains (only web traffic)

Field	Group	Type	⌘	🍏	📱
Total network traffic	Volume	Aggregate	⌘	🍏	📱
	Total network traffic (incoming and outgoing)				

Total web traffic	Volume	Aggregate	#	🍏	📱
	Total web traffic (incoming and outgoing)				

Changes in boot and logon duration

There are now two different ways to look at boot and logon duration.

Aggregate values

The following values represent the duration of boots and logons which happened during the timeframe of the investigation. If no boot or logon happened during this timeframe, then a dash (-) is reported.

Field	Group	Type	#	🍏	📱
Average system boot duration	Startup	Aggregate	#	🍏	📱
	Indicates the average system boot duration.				
Average user logon duration	Startup	Aggregate	#	🍏	📱
	Indicates the average user logon duration.				

Baseline values

The downside of the two aggregate values presented above is that if no boots or logon happened for a device during the investigation period, then no value is reported. For this reason we provide two additional values representing the moving average of boot and logon times. The values do not depend on the time frame specified in the investigation.

Field	Group	Type	#	🍏	📱
System boot duration baseline	Startup	Field	#	🍏	📱
	Indicates the system boot duration averaged over the last boots. In the calculation, recent boots weigh more than older boots (exponentially weighted moving average).				
User logon duration baseline	Startup	Field	#	🍏	📱
	Indicates the user logon duration averaged over the last logons. In the calculation, recent logons				

weigh more than older
logons (exponentially
weighted moving average).

What's new in V6.1

New features

With V6.1, Nexthink fully supports migrations from earlier versions of the product. Moreover, V6.1 Engines can be optimized to store up to twice the amount of history with respect to V5.

Ready for migration

With this new release, Nexthink supports migrations from Nexthink V5.3. In order to simplify the migration process, V6.1 Portal can display, in read-only mode, legacy V5 dashboards. Existing customers can contact their account manager for a personalized migration offer.

Up to 2x history length in the Engine

Thanks to new compression algorithms, Engines can be configured to retain up to twice the amount of history, without any additional hardware requirements and with negligible loss of precision. Existing customers can contact Nexthink Customer Success Services to discuss the best data optimization strategy for their infrastructure.

A new anonymization mode

A new data anonymization mode has been introduced to make users and devices anonymous. This feature is in response to specific customer requests. For instance this mode can be applied to users who need to know if a service is functioning well, but do not need to know if any specific user has a problem. Find out more

Updater

The Nexthink Updater is again being shipped as part of the product. Please note that V6 Collector requires V6 Updater: existing customers relying on Nexthink Updater need to switch to version 6 in order to upgrade Collectors to V6. Find out more

Data-model changes

Metrics

Successful HTTP requests ratio

A new aggregate **Successful HTTP requests ratio** is now available in metrics. This aggregate can be used to track HTTP web services client and server errors.

Forbidden aggregates

Count metrics with a group-by referring to a different object no longer support aggregates conditions which include the value 0 (zero).

What's new in V6.0

New features

Whether you are CIO, IT Manager, Administrator, or an interested line of business manager, End-user Analytics is changing the way IT organizations are aligning their operations with the needs of the business and the end-user. With the V6 release, Nextthink is enabling organizations to accelerate and simplify the management and transformation of their complex IT infrastructure and amid rapidly changing business requirements and end-user work styles.

A brand new Portal

The simple, modern, flat look and feel of Portal V6 brings all focus on the data.

- The separation of the metric definition and UI presentation brings more power to you: now easily define the metrics that you want to compute and then combine them in your favorite visualizations. Find out more about [Creating A Metric](#) and [Following The Evolution Of A Metric](#).
- Time and location have been unified in dashboards allowing you to compare data at a glance as you navigate. Find out more
- The new layout manager in Portal V6 based on award winning visual concepts allows you to easily arrange elements in a dashboard, any way you want and it always looks great! With new widgets, graph types, immediate previews and simplified steps designing and sharing custom and role-based dashboards is now a matter of minutes. Find out more
- The new service overview dashboard in Portal V6 helps you understand at a glance the status of all your IT services from the perspective of the end-users, in real-time. New service detail dashboards help you quickly understand how a service is used, where problems are located and identify users that are impacted. Find out more

User view

The new User View in Finder V6 presents all devices, information, activities, issues, changes and services related to an end-user, all in one place and against one timeline. In one click understand if an event or issue is reoccurring for a

specific user, since when and how often. New drill downs will accelerate problem identification and resolution by enabling you to check how many end-users are affected by similar patterns. Find out more

Server Collector

Extend your End-user Analytics with Windows Server Collector V6 to go beyond the first destination and start discovering, mapping and understanding end-to-end dependencies related to the end-user experience and service consumption while increasing overall security and compliance.

Content centralization

In the new V6 platform metrics, services, and categories are centralized and automatically synchronized across all Engines. Find out more

- Changes in categories and services are automatically reflected in dependent metrics and services to simplify the configuration.
- Metrics can be easily created in Finder starting from an investigation, and few click later you will be visualizing them in your Portal dashboard. Find out more
- Service thresholds are defined directly within Finder. Find out more
- Finder automatically proposes the list of available Engines during connection ? login once, and switch Engine in 3 seconds. Find out more

New system requirements

Portal hardware requirements

The number of cores required by the Portal appliance has been changed for large installations (starting from 20k devices). See Hardware Requirements for more information.

Connectivity requirements

V6 Finder connects to Portal using port 443 for authentication and managing centralized content. To support this, Engine connects to Portal using three additional ports: 7000, 7001 and 7002. See Connectivity Requirements for more information.

Data-model and API changes

Device

Device type

The field **Device type** now includes values **server** and **mobile**.

Number of logical processors

Added a new field **Number of logical processors** representing the total number of threads seen by the operating system.

Entity

The **Entity** field replaces the V5 ***Entity** category. Finder will automatically migrate investigations, one-click investigations and alerts.

Last system update

The semantic of **Last system update** has been modified to take into account only the last successful system update; moreover the value is now updated even when other tools (such as SCCM) are used to deploy Windows updates.

IO and page faults

The fields **High IO throughput time** and **High page faults time** can no longer be used with condition on Activities and Events.

NXT protocol

The syntax used to authorize and authenticate a user using the NXT protocol has been modified. See Bidirectional Integration With The Finder for more information.

Deprecated features

Data model

OS version

The field **OS version** has been deprecated in favor of **OS version and architecture**. The Finder automatically migrates those existing investigations, one-click investigations, and alerts that use the deprecated field.

Portal features

Types of widgets

Dashboards have been completely reworked to be visually more appealing and easier to create. In V6, the widgets included in dashboards are directly linked to the new concept of metrics. Therefore, all V5-style widgets have been deprecated, except for the software metering widget (at least partially).

Widget-related alerts

To unify the methods of alerting users, no widget has the ability to independently send email alerts to selected recipients anymore. That includes the software metering widget, even if this widget remains in the V5-style.

VDI assessment and capacity planning

The VDI assessment and capacity planning module is no longer included in the Portal. Corresponding features will be re-introduced in a later product release.

Portal reports

Reports in Microsoft Word format are no longer included in the Portal. An improved version will be included in a later product release.

Finder features

The **Compare with** tool in the **Timeline** tab of the device view has been deprecated. It is kept in the **Properties** tab of the device view, and it appears in the same tab of the new user view.